

TECHNICAL DATA SHEET

FEBRUARY 2019

BAXBOARD WATERPROOFING PASTE

DESCRIPTION

Baxboard Waterproofing Paste is a ready to use polymeric liquid coating that is applied as a one or two coat system to create a permanently flexible waterproof membrane prior to tiling in wet rooms, showers etc. It can also be used on balconies and covered external areas

ADVANTAGES

- Ready to use.
- Low odour.
- Permanently flexible and waterproof.
- Easy application.
- Solvent free.
- Water clean-up.

USE ON

- Showers, wet rooms, bathrooms and balconies etc., both walls and floors.

TECHNICAL INFORMATION

Appearance	Blue viscous paste
Specific gravity	ca 1.35
Application temperature	5°c – 35°c
Solids content	ca 65%
Drying time	Approx. 3 hours dependant on temperature and humidity
Tile on time	12 hours
VOC content	EC 1 Plus
Coverage	4 – 7.5 m ² per 5 litre

PREPARATION

Substrate should be clean and primed with Baxboard primer.

Any gaps or cracks should be filled with a cementitious filler or acrylic sealant. (Solvent based sealants should not be used).

APPLICATION

Stir the paste before use.

Apply using a brush or roller in one or two coats to give a minimum dry film thickness of 0.5mm on walls and 1.5mm on floors.

Joints and corners should be reinforced with Baxboard tape and pre-formed corners as per installation directions.

If only one coat is to be applied care must be taken to ensure full coverage with no thin patches or missed areas. If two coats are to be applied apply second coat at 90° degrees to first coat application direction, second coat to be applied after a minimum 6 hours.

LIMITATIONS

Not suitable for swimming pools or areas with permanent standing water.

Do not apply if temperature is 5°C and falling.

STORAGE

Store above freezing and out of direct sunlight.

Shelf life is minimum 12 months when stored correctly.

HEALTH AND SAFETY

The product is classed as non-hazardous, but as with all chemical products good industrial hygiene should be observed. Avoid skin and eye contact, wear gloves and goggles. Wash off any splashes with clean water. See S.D.S for full details.

DISCLAIMER

To the best of our knowledge and belief, this information is true and accurate, but as conditions of use and any labour involved are beyond our control, the end user must satisfy himself by prior testing that the product is suitable for his specific application, and no responsibility can be accepted, or any warranty given by our Representatives, Agents or Distributors. Products are sold subject to our Standard Conditions of Sale and the end user should ensure that he has consulted our latest literature.
